

# Belt washer BW-60



## **Operating principle**

The belt washer type BW-60 is made for washing of vegetables and fruit in small and medium-sized quantities.

The product is loaded onto the interwoven mesh belt and transported through the tunnel. Inside the tunnel there are belt sprinklers / nozzles which are mounted underneath and above the belt, which produce an intensive washing action over the product. In the first section the product is thoroughly washed with recirculated water. In the second section the product is rinsed with fresh water.

Dwell times can be altered through a frequency controlled motor which can deliver parameters from 2 and 14 m/min (6 - 42 ft/min).

The machine is almost completely manufactured of stainless steel and is fully mobile mounted on stainless steel castors. The washing process can be continually viewed through a polycarbonate window. The water re-circulation tank and pump system can be easily accessed and drained through a large inspection door.

# **Capacity**

The capacity is dependent on the type of product and the desired cleaning intensity.

### Scope of supply

- > one pump
- > electrical equipment
- > belt tension/release system

#### **Features**

- > multi functional mobile washer
- full stainless steel construction and FDA approved parts
- > variable belt speed to control washing
- > easy access for sanitation control



## **Product specification**

The belt washer is suitable for sanitising all vegetables and washing of carrots, celeriac and fruit.

#### **Technical data**

Voltage:

Total installed power:

Weight:

Dimensions (LxWxH):

Feeding-in height:

Belt length:

Length washing section:

Belt width: Belt speed:

Transfer height (max.):

230/400 V, 3 ph, 50/60 Hz

6,25 KW

approx. 500 kg (1,100 lbs)

3.200 x 1.100 x 1.300 mm (126" x 43" x 51")

900 mm ± 100 mm (35" ± 4")

3.200 mm (126") 2.000 mm (79")

600 mm (24") 2.6 - 14 m/min. continuous adjustable (8 - 42 ft/min)

250 mm

Sormac B.V. Alterations reserved

P.O. Box 419 Telephone: +31 (0)77 351 84 44

NL-5900 AK Venlo Fax: +31 (0)77 320 48 01

Huiskensstraat 68 E-mail: info@sormac.nl NL-5916 PN Venlo Internet: www.sormac.nl