

ORIGINAL
HENKELMAN
vacuum systems



ORIGINAL
HENKELMAN
vacuum systems

Henkelman BV
PO Box 2117
5202 CC 's-Hertogenbosch
The Netherlands
Tel +31 (0)73 - 621 36 71
Fax +31 (0)73 - 622 13 18
info@henkelman.com
www.henkelman.com

Your distributor

'PURE VACUUM'
STANDS FOR HENKELMAN'S CLEAR DESIGN
AND HIGH PERFORMANCE
VACUUM PACKAGING TECHNOLOGY

HENKELMAN SERIES

HENKELMAN, PURE VACUUM

Henkelman is specialised in the development, production and distribution of state-of-the-art vacuum packaging machines. Our leading position in the field of vacuum technology sets us apart from the competition with the largest and most varied range of solutions for the vacuum packaging of food and other products. This is why companies in all types of sectors across the world choose the reliability of Henkelman.

Our machines are 'Made in Holland'. And you can tell. They combine a tightly crafted and functional design with optimum ease of operation and a long life span. Installation is just a matter of 'plug & pack', and the smart design ensures that hygiene standards are maintained at all times.

You can be sure that your machine will be delivered quickly, thanks to Henkelman's extensive international network of authorised dealers. This network guarantees a high-quality, personalised service and a rapid, efficient response to any questions you may have. Henkelman, pure for an optimum packaging process...

Pure
Vacuum



JUMBO
SERIES



BOXER
SERIES



LYNX
SERIES



MARLIN
SERIES



FALCON
SERIES



POLAR
SERIES

LYNX SERIES




LYNX 32




UNIVERSAL TROLLEY



LYNX 42



Full color crystal clear LED screen



- Capacity pump 008 m³/h
- Machine cycle 15-30 sec.
- Dimensions (l x w x h) 534 x 400 x 385 mm
- Weight 35 kg
- Voltage 230V-1-50 Hz (other voltages available)
- Power 0,5 kW

- Dimensions (l x w x h) 570 x 480 x 610 mm
- Swivel castors lock & brake
- Extended mobility
- Labels and pouches storage
- Optimal use of space



- Capacity pump 016 m³/h
- Machine cycle 15-30 sec.
- Dimensions (l x w x h) 534 x 480 x 396 mm
- Weight 46 kg
- Voltage 230V-1-50 Hz (other voltages available)
- Power 0,7 kW

- Direct thermal Label printer (Zebra Technologies)
- Programmable content of label (production / expiry date, product name, storage temperature, gas mixtures, etc.)
- Possibility of multiple labels / cycle
- Backing foil remover

LYNX SERIES

INNOVATIVE AND INTELLIGENT VACUUM PACKAGING MACHINES WITH WORLD WIDE REPUTATION

- High quality compact table models
- Pure and attractive Design
- Intelligent full colour Control Interface
- Extensive packaging parameters for specific packaging requirements
- Full HACCP compatible with labelling device
- Easy clean concept

FOOD PRODUCTS

Retail Trade - Restaurants - Catering - Supermarkets
(meat, poultry, fish, cheese, vegetables etc.)

- No contamination or bacteria's multiplication, hence an extended shelf life resulting in:
 - cost savings (larger purchasing orders, efficient cooking time spreading and diminution of products losses)
 - turnover increase (more variation and spread in product range)
- Optimal product and storage hygiene (hermetically sealed)
- No loss of product (prevents drying out, moulds and freeze burn)
- Improved product quality (product maturing in packaging, no loss of aroma)
- Professional product presentation
- Optimal packaging contributes to food safety and HACCP standards
- Ideal for Sous-vide Cuisine applications

NON-FOOD PRODUCTS

Electronics - Semi-conductors - Metal - Pharmaceutical Products - Textiles - Laboratories etc.

- Moisture free packaging
- Air and dust free packaging
- Volume reducing packaging
- Scrapes and scratches free solution
- Fraud resistant packaging
- Sterile and contamination free packaging

SPECIFICATIONS

GENERAL

- Compact Table top model
- Innovative Intelligent Design
- High volume transparent lid
- Easy clean flat working plate
- Removable wireless sealing bars
- Insert plates for fast cycle and product adjustment
- Full colour wide screen
- User friendly interface
- 6 languages operational mode
- 20 programs adjustable in % and mbar/ hPa
- USB port for data transfer
- Printing and Labelling function
- Service data storage
- Program access security
- In compliance with HACCP regulations

PACKAGING FUNCTIONS

- Vacuum
 - Optimal final vacuum 99,80% (2 mbar)
- Gas-flush
 - Injecting food-gas for product protection and longer shelf life
- Soft-air
 - Controlled ventilation for protection of product and packaging

SEALING SYSTEMS

- Double Seal
 - 2 x 3,5 mm convex sealing wires for product remains elimination and strong hermetic seals.
- Cut-off seal
 - 1 x 3,5 mm convex sealing wire + 1 x 1.1 mm round cutting wire / One time setting (cut off remaining flap)
- 1-2 Cut-off seal
 - 1 x 3,5 mm convex sealing wire + 1 x 1.1 mm round cutting wire / Independent time setting (shrink bags)
- Wide Seal
 - 1 x 8.0 mm flat sealing wire

CONTROL FUNCTIONS

- Sensor Control
 - Set percentage or pressure for vacuum and gas functions for accurate and constant packaging results /Automatic programming / 20 default programs / Vacuum plus time / Red meat device / Sequential vacuum
- Quick stop H₂O Sensor Control
 - Set percentage pressure for vacuum and detect boiling point of the product. For fast cycle and better food protection Automatic programming / 20 default programs / Vacuum plus time / Red meat device / Sequential vacuum

SUPPORT CONTROL FUNCTIONS

- STOP button for full cycle interruption
- Digital maintenance program for pump / Operating hours counter / Service indicator program

ACCESSORIES

- Compact label printer (Zebra Technologies)
- Inclined insert plate for packaging liquid products
- Service kit for standard maintenance
- Trolley with shelves and castors

Optional

Standard

Sentence and printing errors reserved



Pure Vacuum